

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## MANUFACTURE OF THIN FILM TRANSISTOR

Patent Number: JP63316470  
 Publication date: 1988-12-23  
 Inventor(s): OKABE KAZUYA; others: 03  
 Applicant(s): ALPS ELECTRIC CO LTD  
 Requested Patent: ☐ JP63316470  
 Application Number: JP19870152659 19870619  
 Priority Number(s):  
 IPC Classification: H01L27/12, H01L29/78  
 EC Classification:  
 Equivalents: JP2656495B2

### Abstract

**PURPOSE:** To prevent reduction clouding of ITO, by using source/drain electrodes, which are formed on an n layer, as masks and etching the n layer, and next by forming a passivation layer immediately and afterwards etching a passivation layer and a picture element at the same time.

**CONSTITUTION:** A gate electrode 2, a picture element electrode 3 made of ITO (indium, tin oxide) materials and the like, a gate electrode layer 4, a semiconductor layer 5, and an n<+> layer 9 are formed on a substrate. A contact hole 10 is formed, and a source electrode 6 and a drain electrode 7 are formed of Al materials or the like on the n<+> layer 9. Next both these electrodes are used as masks to perform n<+> layer etching. The n<+> layer 9 is divided into two parts; a source region 5a and a drain region 5b, and a passivation layer 8 is formed thereon of silicon nitride materials or the like. Picture element etching, in which respective layers laminated on the picture element electrode 3 are removed to expose the picture element electrode 3, and passivation layer etching, in which passivation layers 8 on respective gate and source terminal parts of a thin film transistor are removed, are performed at the same time. Hence the clouding of the ITO can be prevented.

Data supplied from the esp@cenet database - I2